

<b>TECHNICAL SPECIFICATIONS</b>	
<b>DESCRIPTION</b>	<b>600 LTRS</b>
<b>Tank :</b>	
Capacity	600 litter
Material	Polyethylene
Agitation	Hydraulic
Level indicator	Graduated circular dial
<b>Pump :</b>	
Type	Triplex plunger pumping unit (Diaphragm Optional)
Capacity	55 litter per minute (70 liter optional )
Working pressure	40 bars or 600 PSI
Recommended working pressure	1-10 bars or 15-300 PSI
RPM	900
<b>Filter :</b>	
Capacity	80 liters/minute
Mesh size	50 mesh
Flush out	Manually
<b>Control Unit :</b>	
Manifold	3 sections operated with Pressure gage, Pressure regulator valve
<b>Boom :</b>	
Width	10 meters / 33' feet
Height Adjustment	Manually up to 24" inches (61 cm) / (Note : up to 6' feet optional)
Type	Wet Boom
Actuation	Manual
Nozzle spacing	20 inches (50 CM)
Number of nozzles	20 nozzles
Nozzle Tip Brand & Material	Teejet® & Polymer (ceramic Optional in this model)
Working speed	2-6 km/hour
Extra Accessories	3 no. of nozzles tips, tip filters, Pump Kit, Tool Box, Gas Kit Etc.
Tractor Hp	60HP - 75HP